



# Automated Door Systems

## Entry System - Key Pad

### OVERVIEW

#### GALEO

A new stylish, vandal-resistant, backlit keypad for 100 users with remote electronics for high security applications. The Galeo has modern styling with blue back-lit keys. Models: 1-Relay (GALEO), 2-Relay (GALEO-2R) 3-Relay (GALEO-3R)

- \* Stylish Back-Lit Keypad
- \* Ergonomic Design
- \* Shallow Profile
- \* Remote Electronics
- \* 12 - 48Vdc Free Voltage
- \* 12 - 24Vac Free Voltage
- \* Stand Alone
- \* 100 User Codes
- \* 1, 2 or 3 Relay Outputs
- \* IP67 Weather Resistant
- \* Audible Indicator
- \* User Code Changes
- \* Easy Install



#### Specification

Voltage: 12-48Vdc or 12-24Vac  
 Current: 10mA Passive, 100mA Active  
 Users: 100 Individual Codes  
 Dimensions: 100 x 75 x 15mm (h x w x d)  
 Environmental: IP67, -20 to +50C  
 Electronics: Remote (included)  
 Inputs: Exit Button & Timer Input  
 Outputs: 1-3 Relay Outputs, Timed or Latch  
 Programming: Via Master Code

#### KCIEN



KCIEN is a rugged stainless KCIEN steel keypad with soft blue backlighting. Ideal for harsh environments, the KCIEN has 1 relay output.

KCIEN-PB is identical to the KCIEN, but it includes a push-button for other uses such as being connected to a door bell.

### CBB Keypads



#### Dimensions:

- \* Stainless Flush (CAA)
- \* Stainless Surface (CBB)
- \* 12/24v AC/DC
- \* Stand Alone
- \* 100 User Codes
- \* 3 Relay Outputs
- \* Weather Resistant
- \* LED Indicators
- \* Braille Buttons
- \* User Code Changes
- \* Easy Install

#### Specification

Voltage: 12/24v ac/dc  
 Current: 10mA Passive, 100mA Active  
 Users: 100 Individual Codes  
 Dimensions: 120 x 105 x 45mm (h x w x d) - CAA  
 125 x 105 x 65mm (h x w x d) - CBB  
 Environmental: IP63, -20 to +50C  
 Inputs: Exit Button & Timer Input  
 Outputs: 3 Relay Outputs, Timed Latch Mode Relays 1 & 2